



4900 Series Auto Security Revolving Door



DESIGNED FOR SECURITY ACCESS CONTROL AND EMPLOYEE PROTECTION FOR
ONLY A FRACTION OF THE COST OF MANNED ENTRANCES

- Narrow line, aesthetically appealing, easy to maintain automatic security door
- Allows for simultaneous two-way traffic and continuous operation
- Automatic hands-free operation and electronic sensing for reliable operation, with standard anti-tailgating feature
- Optional Anti Piggybacking features are available
- PLC based programmable controller integrates with all access systems
- Finished floor mount application for retrofit to existing facilities
- Door design meets ANSI/BMHA Standard 156.27

All Specifications are Subject to Change



4900 Series Auto Security Revolving Door

Description	Standard Configuration	Options
Diameters	6', 6'-6" or 7' (1828, 1980, 2134 mm)	Custom diameters available
Heights	7' (2134 mm) door opening height	Consult factory
Canopy	12" (305 mm) minimum, round, 1 piece	Consult factory
wings	4 wing locked in position	
stiles	narrow	Custom options, clad
locks	2 concealed in bottom rail	
Wing glass	¼" (6 mm)	½" (12 mm), 32 mm bullet resistant, custom designs
Drum wall	curved enclosure	
Access control	One or two way security	
Safety Sensors	Corner post Bumpers	
Lights		3 ¼" LED (83 mm)
Finish	Anodized aluminum, clear, bronze	Rushclad cladding, paint
Roof	Standard aluminum	Full circular to match finish
Ceiling	Pie shaped Segments for easy access	
Design/Testing	ASTM 156.27	Speakers/enunciator
Sensors	Flush Ceiling mounted anti-tailgating sensors	Anti piggybacking Sensor System
Card reader bracket		As per Customer request
Power	120 VAC 20 Amp Dedicated Circuit	Additional 120 VAC 15A for lights

4900 Series Security Door Features and Specifications:

For more options, consult your C J Rush sales representative

All Specifications are Subject to Change